## StarX



## StarX

HIGH PERFORMANCE PAD



pad properties

the highly developed StarX pad possess the following outstanding features: antistatic behaviour - outstanding antistatic behavior allows for a perfect ink transfer without practically any ink splashes on the edges or ink remaining on the pad.

resistance - unparalleled mechanical resistance enables longer pad lifespans, even when printing over sharp edges of the printed part.

no swelling - swelling on the pad surface from solvents, ink and repeated pad to part compressions are eliminated.

user friendly - StarX pads require only a few seconds to be activated by briefly cleaning the surface of the pad with thinner. These pads should only be stored shaded from direct sunlight and not in contact with other objects.

## pad types

The StarX high performance pads can be purchased in varying degrees of hardness. On delivery their hardness tolerance is +\-2 Shore-00.

Shore*	remarks	
62 Shore-00	very hard, e.g. for textured surfaces	
54 Shore-00	normal hardness – most often used hardness	
44 Shore-00 soft – especially good for rounded or curved components		
39 Shore-00	very soft – for delicate and breakable components	

The pad hardness must be stated on ordering the pad.

e.g.: T0142-64	T = pad
e.g.: 1497-44	T = pad









Group 1: ROUND	Group 2: RING SHAPED
pads for round print images	pads for ring shaped images
Group 3: SQUARE	Group 4: RECTANGULAR
pads for square shaped images	pads for rectangular shaped images
Group 5: special pads pads for problematic prints	rotary printing pads pad holders

0142 = pad number

1497 = pad number



Or download the pad catalog (pdf-Format) from our website:

www.padprinting.biz www.tampographie.bi www.tampondruck.biz www.teca-print.com

Teca-Print Teca-Print AG Postfach Bohlstrasse 17

CH-8240 Thayngen

Tel. +41 (0)52 645 2000 Tel. +41 (0)52 FON TECA Fax +41 (0)52 645 2102 info@teca-print.com teca-print.com

9. 237 / 000 706